

SINCE **TONGDA** 1952

Create a better life

SHANGDONG TONGDA TEXTILE MACHINERY (GROUP) CO. LTD



Combing Machine Model : FA588

Technical Specification :

Head : 8

Number of Delivery : 1

Automatic can change with

Head Distance : 470 mm

Speed : 60, 280, 300, 320 nips according to different process

Bobbin Size : 200x300 mm (inner 180 mm, out Φ 200x300 mm)

Feed Lap : Width: 300mm; dia: less then 600 mm

Lap Count : 60-80 ktex,

Fiber Length : 20-50 mm

Noil : 8-25%

Feed Length Per Nipper : 4.3/4.7/5.2/5.9 (standard: 5.2)

Drafting Type : 3 over 3 or latest curve drafting, pneumatic load

Draft Ratio : Pre-draft: 1.14; 1.36; 1.5; total draft: 9-19.3

Draft Gauge : Main draft : 41-54

Coiling Style : Single can sing coiling

Sliver Can Size : Φ 600x1200 mm (with caster)

Comber Sliver : Count 3-6 ktex

Suction Style : Central suction

Compressed Air : Pressure : 6-8x105 pa Or 0.6-0.8 mpa

Capacity : 1.5 m3/h

Exhaust Air Volume : 3000 m3/h

Suction Pressure : 250 pa

Source of Electricity : 380 v $\pm$ 10%; 50 Hz

Auto Counter : Meter & 4 shift

Motor Power : Inverter motor 3.5 kw-4.7 kw; brush motor 1.3 kw (approx)

Tongda Industry Park, Tongda Road, Changyi Weifang ,China

Tel:0086-532-8092260, Fax: 008653280922607

Email: sales@china-tongda.com, www.china-tongda.com

SINCE **TONGDA** 1952

Create a better life

SHANGDONG TONGDA TEXTILE MACHINERY (GROUP) CO. LTD

Suction Motor : 1.5 kw, if the suction style is group suction,
then this suction motor is not necessary.

Top Comb Graf : 26 N/CM

Coiler Trumpet : 3.4, 3.7, 4.1

Change Gear & Pulley : Complement

Top Roller Cots : Becker

Overall Size : 7145×2145×1700 mm (approx)

U% : <3.5%,

Neps : <50

Machine Weight : 5000 kgs (approx)